

## Vtoková mříž v litinovém rámu

D400 - těžké dopravní zatížení

# Standard



Kód	<b>KML26</b>
Materiál	<b>Litina</b>
Hmotnost	<b>108 kg</b>
Norma	<b>DIN19583, DIN1229, EN124-2</b>
Balení	<b>16 ks/pal</b>
Třída zatížení	<b>D400</b>

Mříž 500x500mm pro uliční vpusti.

### VÍKO:

- | Mříž rovná mezi žebry 35 mm
- | Rozebíratelné spojení mříže s rámem
- | Vtokový průřez 910 cm<sup>2</sup>

### RÁM:

- | Litinový rám s osazením pro lapač
- | výška rámu 100 mm

### OSTATNÍ:

- | Osadit na vyrovnávací prstenec 10A.
- | Mezi rámem a vrchním dílem vpusti musí být alespoň 20mm vysoké maltové spojení s pevností min.45MPa

**Warning:** file\_exists(): open\_basedir restriction in effect.

File(/var/www/clients/client1/web105/web/media/product/image/4767.png) is not within the allowed path(s):

(/var/www/clients/client1/web105/web:/var/www/clients/client1/web105/private:/var/www/clients/client1/web105/tmp:/var/www/kasi-dev2.vicko.cz/web:/usr/share/php5:/usr/share/php:/tmp:/usr/share/phpmyadmin:/etc/phpmyadmin:/var/lib/phpmyadmin:/var/www/clients/client1/web98/web/media

in **/var/www/clients/client1/web105/web/app/model/product/ProductImageManager.php** on line **272**

**Warning:** file\_exists(): open\_basedir restriction in effect. File(/var/www/clients/client1/web105/web/media/product/technical/4767.png) is not within the allowed path(s): (/var/www/clients/client1/web105/web:/var/www/clients/client1/web105/private:/var/www/clients/client1/web105/tmp:/var/www/kasi-dev2.vicko.cz/web:/usr/share/php5:/usr/share/php:/tmp:/usr/share/phpmyadmin:/etc/phpmyadmin:/var/lib/phpmyadmin:/var/www/clients/client1/web98/web/media

in **/var/www/clients/client1/web105/web/app/model/product/ProductImageManager.php** on line **272**



**ODVOD  
DEŠŤOVÝCH VOD**

